



Landscape Depot & Masonry Products

VISIT OUR  
10,000 SQ. FT.

**SHOWROOM**



## Maintaining and Improving Interlocking Pavers

### Step 1 - Washing

Even if your interlock pavers are worn down and tired looking, they can still be restored to their original beauty after proper treatment of washing and sealing. Stains on your interlock such as oil, gum, rust, gas etc can usually be removed with cleaning products. Power wash your interlock and allow the surface to dry completely

### Step 2 – Polymeric Sanding

After the Washing phase, your interlock will have no jointing sand remaining. Replace with new, fresh and strong polymeric sand. Polymeric sand is jointing sand

mixed with polymers specially formulated to fill the joints in pavers and stones. As well, it helps inhibit weed growth and deters ants and other insects. Sweep it into the cracks being careful not to leave any on the actual paver surface. Dampen to activate the polymers and solidify the pavers.

### Step 3 – Sealing

Once completely dry, the sealer can be applied. Sealers intensify the paver colors and protect from stain penetration. Apply with a brush, roller or sprayer. Sealers are available in natural sheen, semi gloss and wet look.



We sell our bulk soils, mulches & aggregates now in 1 yard totes.

**10% OFF**  
**Interlock Cleaners**  
**& Sealers**

Expires June 29, 2013

**905-873-8988**

44 Armstrong Avenue, Georgetown

**peellandscapedepot.com**