CANADIAN



ANADIAN



CANADIANA SNOWBLOWERS

Fully serviced and set up in OUR Service Department

EXCLUSIVE PERFORMANCE FEATURES-

- 1 ENGINE: -- 5 H.P. 8 H.P. or 10 H. P. 4 cycle, fully winterized.
- 2 FRICTION DRIVE SPEED SHIFT: Instant response fivespeeds forward plus power reverse offers speeds for varying snow conditions.
- 3 FRICTION DISC DRIVE: Changes ratios by the clashless process of moving the edge of one friction disc inward or outward across the face of another.
- 4 DRIVE CLUTCH: "DEAD MAN" clutch is a finger tip operated lever conveniently mounted on handle to ensure maximum operator safety.
- 5 LIMITED SLIP DIFFERENTIAL: Adjustable from differential wheel action to straight through power train action.
- 6 AUGER CLUTCH SYSTEM: Governs power supply to the impeller and auger.
- 7) ADJUSTABLE DEFLECTOR: Hand operated "worm spring" driven crank rotates chute in a 210 degree arc.
- 8 TWO STAGE AUGER SYSTEM: 1st STAGE: slow turning auger cuts snow and feeds it into the impeller sealed ball bearings are used on both ends of auger shaft left and right uugers are shear bolt mounted with grease fittings to ensure shearing action on impact.

2nd STAGE: — snow is ted into high speed impeller where it is forced out of the directional discharge chute. — hardened worm gear drive between the two stages is contained in a cast housing with sea of ball bearing side support plates.

- 9 HANDLE BARS. 11/4" diameter, 14 gauge painted tubular steel construction complete with rubber hand grips.
- 10 CONTROL CONSOLE: Enclosed handle mounted within one hand reach
- 11) TIRES: fully pneumatic wide low profile traction tires.
- 12 DRIF CUTTERS: Optional on all models.

CHECK AND COMPARE

- → Best value for your dollar
- Canadian made products
- ✓ Same day service if required
- ✓ 8 models to choose from
- Instant parts & service
- ✓ We take trades
- Financing and lay-away available

WE WILL NOT KNOWINGLY BE UNDERSOLD

WE SERVICE EVERYTHING WE SELL ON OUR PREMISES

NORSIM EQUIPMENT

538 Bay St (beside the Bike Shop), Midland 526-4262