



TESTED 350 LBS.
 FIRE EXTINGUISHER
ALERT
 EXTINCTEUR A INCENDIE

**TO OPERATE
 TURN BOTTOM UP**

CHARGING DIRECTIONS
 ADD ONE LB. BI-CARBONATE OF SODA INTO TANK AND
 WATER TO INSIDE PROJECTION. STIR WELL. FILL BOTTLE
 WITH FLUID (4 FLUID OUNCES) OF SULPHURIC ACID FIT BY
 NEEDLE SCREW COVER ON TIGHT. GLEAK DO NOT
 TOUCH AND RECHARGE ONCE A YEAR OR IMMEDIATELY
 AFTER BOARD HAVE LAST CHARGED ON CARD ATTACHED.
 PROTECT FROM FREEZING

**POUR OPERERER
 RENVERSEZ**

POUR RECHARGER
 AJOUTER UN LBS. DE BI-CARBONATE DE SODA A PROJECTION EN DEDANS A TOUT
 L'EAU. MELER BIEN. REMPLIR LA BOUTEILLE AVEC LE FLUIDE (4 ONCES)
 D'ACIDE SULFURIQUE. SERRER LA VISSEUSE A TRES BIEN. NE PAS TOUCHER
 ET RECHARGER UNE FOIS L'AN OU IMMEDIATEMENT APRES
 LA DERNIERE CHARGE. SUR LA CARTE ATTACHEE. PROTEGER CONTRE LA GEELE

K. RANGBURN & CO. TORONTO, ONTARIO