

TESTED 350 LBS.
FIRE EXTINGUISHER
A L E R T
EXTINCTEUR A INCENDIE

**TO OPERATE
TURN BOTTOM UP**

CHARGING DIRECTIONS
POUR LES LBS. BI-CARBONATE DE SODA INTO TANK ADD
WATER UP TO INSIDE PROJECTION. STIR WELL. FILL BOTTLE
WITH (4 FLUID OUNCES) OF SULPHURIC ACID. PUT ST-
OPPER IN BOTTLE. SCREW COVER ON TIGHT. CLEAN OUT
THOROUGHLY AND RECHARGE ONCE A YEAR OR IMMEDIATELY
AFTER USE. RECORD DATE LAST CHARGED ON CARD ATTACHED.
PROTECT FROM FREEZING

**POUR OPERERER
RENVERSEZ**

POUR RECHARGER
COMPLIET DE BI-CARBONATE DE SODA EN DEDANS. AJOUTER
L'EAU JUSQU'A LA PROJECTION EN DEDANS. BRASSER
BONNEMENT. AJOUTER (4 ONCES FLUIDES) JUSQU'A LA MAR-
QUE INFERIEURE. COUVER LA BU BOURCHON EN
VITTE. BIEN LA TETE. APRES USAGE PARTIR
NETTOYER ET RECHARGER UNE FOIS L'AN. INSCRIRE
LA DERNIERE CHARGE SUR LA CARTE ATTACHEE.
PROTEGER CONTRE LA GELEE

FRANCO FIRE ENGINE & CO. MFG. CO.
TORONTO - ONTARIO

Manufactured in Canada
FIRE EXTINGUISHER
NO. 1